

Hedue L1G line laser

Cross line laser with green laser beam for optimum visibility in interior work.

The green laser beam is many times more visible than a red laser beam. This increases the working range to up to 30 m without a laser detector. This simplifies alignment and leveling work indoors and saves you a lot of time.

The compact line laser is designed for construction sites and impresses with its absolutely clean line reproduction. The device is very simple and intuitive to operate, yet has many useful functions.

For leveling work in sunlight, we recommend using a compatible laser detector.



Better visualization of the laser line indoors due to the green laser diode.



Battery status indicator for timely battery replacement.



Connection of all common tripods and mounts with the magnetic multifunction adapter.

Features

- Better visualization of the laser line indoors due to the green laser diode.
- Fast and exact self-levelling via the magnetic pendulum.
- Display of slopes by switching off the self-levelling function.
- Separate switching of the laser diodes.
- Battery status indicator for timely battery replacement.
- Working in bright light and at long distances in conjunction with laser detectors.
- Avoidance of measuring errors through a warning signal when leaving the self-levelling range.
- A horizontal laser line for levelling tasks.
- A vertical laser line for alignment and alignment.
- Connection of all common tripods and mounts with the magnetic multifunction adapter.
- 360° tracking of the laser lines with the tripod.



**360° tracking of the laser lines
with the tripod.**



**Avoidance of measuring errors
through a warning signal when
leaving the self-levelling range.**

**360° tracking of the laser lines
with the tripod.**

Specifications

Self-levelling range horizontal	3°
Vertical self-levelling range	3°
Levelling accuracy	3 mm / 10 m
Working radius without laser detector	15
Working area with laser detector	50
Laser class	II
Laser Diode	2 x 532 nm
Laserfarbe	grün
Operating time in hours	3
Tripod thread	5/8" & 1/4"
IP protection class	IP54
Warranty / Months	24
Type of battery	AA
Number of batteries	3
Operating temperature	-10°C - +40°C
Weight	400 g
EAN	4012589762190

Scope of Delivery

- bag
- Test certificate
- Batteries Alkaline
- [Multifunctional adapter](#)
- QuickstArt
- Mini tripod / adapter
- target plate