

Laser detector hedue E4 (red and green)

Millimeter display of the deviation to the laser beam. Suitable for rotating lasers with red or green laser beam.

The digital display enables height differences to be measured and corrected quickly. The large reception range of 127 mm is an additional aid. The distance to the laser line is displayed in mm or inches.

The robust housing of the hedue E4 laser detector is encased in rubber and protected against dust and water jets in accordance with IP66.

The hedue E4 laser detector is suitable for both rotating lasers with a red or green laser beam.



The display shows the distance to the laser line in mm or Inch.



With optical and acoustic signal

Features

- The display shows the distance to the laser line in mm or Inch.
- Switching the reception sensitivity (coarse/fine)
- Shock and drop protected by encased housing
- With optical and acoustic signal
- With magnetic holder for attachment to carriers
- With integrated spirit level for optimum alignment
- With display on front and back
- For rotary laser with green laser diode
- For rotary laser with red laser diode
- Attachment to measuring sticks with the universal holder.
- Freely selectable zero point within the reception range.

Specifications

Dimensions	160 x 72 x 32 mm
Warranty / Months	24
Type of battery	AA
Number of batteries	2
IP protection class	IP66
Measurement accuracy	1 mm
Work area	600 m
EAN	4012589820340

Scope of Delivery

- Batteries
- Universal cradle